



CHEMAX
CORPORATION

P. O. Box 7453, Beaumont, TX 77726-7453
Phone (409) 866-4232 FAX (409) 866-4424


MATERIAL SAFETY DATA SHEET

EMERGENCY PHONE 1-800-346-0132

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD (HSC) 29 CFR 1910, 1200, STANDARD MUST BE CONSULTED FOR SPECIFIC REQUIREMENTS.

HMIS SYMBOL	
HEALTH	2
FLAMMABILITY	2
REACTIVITY	0

HMIS	NFPA
SEVERE 4	EXTREME
SERIOUS 3	HIGH
MODERATE 2	MODERATE
SLIGHT 1	SLIGHT
MINIMAL 0	INSIGNIFICANT



PRODUCT IDENTIFICATION: A122 COIL-ITE FILTER COTE CPC
DATE: 01/02/03

SECTION I: HAZARDOUS INGREDIENTS

CAS NUMBER	CHEMICAL NAME	%	TLV (PPM)
8052-41-3	PETROLEUM DISTILLATE	20	100
75-28-5	ISOBUTANE	12	1000
64742-54-7	PETROLEUM DISTILLATE	10	5 mg/M3
1338-43-8	SORBITAN MONOOLEATE	5	N/A
7732-18-5	DIONIZED WATER	53	N/A

SECTION II: PHYSICAL DATA

BOILING POINT: N/A
 VAPOR PRESSURE: PSIG @ 70 F (Aerosols)
 VAPOR DENSITY: N/C
 SOLUBILITY IN WATER: EMULSIFIABLE
 SPECIFIC GRAVITY: CONCENTRATE ONLY = 0.910
 PERCENT VOLATILE BY VOLUME: N/A
 EVAPORATION RATE: N/E
 P H: N/A
 APPEARANCE AND ODOR: WHITE CREAMY SPRAY & PINE FRAGRANCE

SECTION III: FIRE AND EXPLOSION DATA

FLASH POINT: N/A
 FLAMMABLE LIMITS: COMBUSTIBLE
 EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER
 SPECIAL FIREFIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS

UNUSUAL FIRE AND EXPLOSION HAZARDS:
 DO NOT EXPOSE TO TEMPERATURES ABOVE 130 F OR CONTAINER MAY RUPTURE

SECTION IV: HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: N/A

EFFECTS OF OVEREXPOSURE: CAN CAUSE HEADACHE; DIZZINESS; ASPHYXIA; ANESTHETIC EFFECTS; POSSIBLE UNCONSCIOUSNESS; NAUSEA; POSSIBLE CHEMICAL PNEUMONITIS IF ASPIRATED INTO LUNGS; CAN CAUSE EYE & SKIN IRRITATION AND SKIN TUMORS

EMERGENCY FIRST AID PROCEDURES:

SKIN: WASH WITH SOAP AND WATER. IF IRRITATED, SEE PHYSICIAN.

EYES: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATED, SEE PHYSICIAN.

INGESTION: DO NOT INDUCE VOMITING.

SEEK IMMEDIATE MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NECESSARY.

SEEK IMMEDIATE MEDICAL ATTENTION.

SECTION V: REACTIVITY DATA

STABILITY DATA: STABLE. AVOID OPEN FLAME, WELDING ARCS, HEAT, AND SPRAKS.

INCOMPATIBILITY: STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI: SPILL OR LEAK PROCEDURES

SMALL SPILLS: ABSORB WITH SUITABLE MEDIUM. INCINERATE OR LANDFILL ACCORDING TO ALL LOCAL/STATE/FEDERAL REGULATIONS. DO NOT FLUSH TO SEWER.

LARGE SPILLS: AEROSOL CANS, WHEN EMPTIED AND DEPRESSURIZED THROUGH NORMAL USE, POSE NO DISPOSAL HAZARD AND SHOULD BE RECYCLED.

AVOID BREATHING OF VAPORS AND ABSORPTION THROUGH SKIN.

FOLLOW STATE AND LOCAL REGULATIONS FOR DISPOSAL OF LARGE NON-RECLAIMABLE SPILLS.

SECTION VII: SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: IF VAPOR CONCENTRATION EXCEEDS TLV, USE RESPIRATOR APPROVED BY U.S. BUREAU OF MINES FOR ORGANIC VAPOR.

VENTILATION: ADEQUATE VENTILATION TO KEEP VAPOR CONCENTRATION BELOW TLV(S)

PROTECTIVE GLOVES: LATEX GLOVES IF SKIN EASILY IRRITATED

EYE PROTECTION: SAFETY GLASSES RECOMMENDED

OTHER PROTECTIVE EQUIPMENT: NONE

REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP & WATER BEFORE HANDLING FOOD.

SECTION VIII: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: DO NOT PUNCTURE OR INCINERATE CONTAINERS. DO NOT STORE AT TEMPERATURES ABOVE 130 F. KEEP OUT OF REACH OF CHILDREN. REMOVE IGNITION SOURCES. AVOID PROLONGED BREATHING OF VAPOR.

OTHER PRECAUTIONS: READ & FOLLOW THE DIRECTIONS ON THE PRODUCT LABEL. THEY ARE YOUR BEST GUIDE TO USING THIS PRODUCT IN THE MOST EFFECTIVE MANNER, AND THEY ALSO GIVE YOU THE NECESSARY SAFETY PRECAUTIONS TO PROTECT YOUR HEALTH.