

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 113840
IDENTITY: PACESETTER EP-65 GREASE
Revision Date: 06/29/2007

Section I

Manufacturer's Name: CHEMAX CORPORATION***	Telephone Numbers:
Address: P. O. BOX 7453	Emergency:
	800/255-3924
BEAUMONT	Information:
State: TX Zip Code: 777267453	409/866-4232

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
HEPTANE	142-82-5	400 PPM	400 PPM	N/A	30-40
PETROLEUM DISTILLATE	8002-05-9	5 MG/M3	5 MG/M3	N/A	25-35
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	20-30
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	156 F	Specific Gravity (water=1)	0.80
Vapor Pressure (mm Hg)	124	Melting Point:	N/A
Vapor Density (AIR=1)	>1	Evaporation Rate:	6
Solubility in Water:	0 %	(Butyl Acetate=1)	

Appearance and Odor: BLUE GREASE, SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): < 20F TCC Flammable Limits: LEL: 1.1 UEL: 7.5
Extinguishing Media: CO2, WATER FOG, FOAM, DRY CHEMICAL
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A
FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 113840

Stability: Unstable: Conditions to avoid: TEMPERATURES ABOVE 120 F
Stable: X
Incompatibility (Materials to Avoid): NONE KNOWN

Hazardous Decomposition or Byproducts: OXIDES OF CARBON, HCL

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: N/A

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS-PROLONGED MAY LEAD TO UNCONSCIOUSNESS. EYES: STRONG
IRRITATION. SKIN: MILD IRRITATION. MAY CAUSE LOCALIZED DEFATTING.
INGESTION: VOMITING, DIZZINESS, NAUSEA, INTESTINAL CRAMPING.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE
WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. SKIN:
WASH THOROUGHLY WITH SOAP AND WATER. EYES: FLUSH WITH WATER FOR 15 MINUTES.
CONTACT PHYSICIAN IF IRRITATION PERSISTS. INGESTION: CONSULT PHYSICIAN

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH
RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL GUIDELINES. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR
HEAT OR OPEN FLAMES. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE
BURSTING.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREA.
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER USE.

□