



CHEMAX
CORPORATION

MATERIAL SAFETY DATA SHEET


EMERGENCY PHONE 1-800-346-0132

P. O. Box 7453, Beaumont, TX 77728-7453
Phone (409) 866-4232 FAX (409) 866-4424

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD (HSC) 29 CFR 1910, 1200, STANDARD MUST BE CONSULTED FOR SPECIFIC REQUIREMENTS.

HMIS SYMBOL	
HEALTH	2
FLAMMABILITY	3
REACTIVITY	0

HMIS		NFPA	
SEVERE	4	EXTREME	
SERIOUS	3	HIGH	
MODERATE	2	MODERATE	
SLIGHT	1	SLIGHT	
MINIMAL	0	INSIGNIFICANT	



PRODUCT IDENTIFICATION: A169 SILICONE AUTO POLISH CPC
DATE: 01/02/03

SECTION I: HAZARDOUS INGREDIENTS

CAS NUMBER	CHEMICAL NAME	%	TLV (PPM)
64742-48-9	ISOPARAFFINIC HYDROCARBON	37-47	400
64742-69-8	PETROLEUM DISTILLATE	10-15	450
63148-62-9	POLYDIMETHYL SILOXANE	2-5	N/A
68476-85-7	LIQUIFIED PETROLEUM GAS	40-50	1000

SECTION II: PHYSICAL DATA

BOILING POINT: N/D
 VAPOR PRESSURE: 56
 VAPOR DENSITY: N/D
 SOLUBILITY IN WATER: NEGLIBIBLE
 SPECIFIC GRAVITY: 1.214
 PERCENT VOLATILE BY VOLUME: > 95
 EVAPORATION RATE: N/D
 P H: N/D
 APPEARANCE AND ODOR: CLEAR, YELLOW LIQUID & MILD, SWEETISH ODOR

SECTION III: FIRE AND EXPLOSION DATA

FLASH POINT: 103 F (T.O.C.)
 FLAMMABLE LIMITS: N/A
 EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL, CARBON DIOXIDE
 SPECIAL FIREFIGHTING PROCEDURES: KEEP CONTAINER COOL. USE EQUIPMENT OR SHIELDING REQUIRED TO PROTECT PERSONEL AGAINST BURSTING, RUPTURING, OR VENTING CONTAINERS. WEAR A SELF-CONTAINED BREATHING APPARATUS.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: TEMPERATURES ABOVE 120 F MAY CAUSE CONTAINERS TO VENT, RUPTURE, OR BURST

SECTION IV: HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: N/A

EFFECTS OF OVEREXPOSURE: MINIMAL BELOW 1000 PPM; DIZZINESS; DROWSINESS; THROAT IRRITANT AT LEVELS ABOVE 1000 PPM; UNCONSCIOUSNESS AND DEATH POSSIBLE ABOVE 10,000 PPM; INGESTION COULD CAUSE GASTRONINTESTINAL IRRITATION AND VOMITING

EMERGENCY FIRST AID PROCEDURES:

SKIN: WASH WITH SOAP AND WATER

EYES: FLUSH WITH WATER WHILE LIFTING UPPER/LOWER LIDS. GET MEDICAL AID.

INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. ASPIRATION OF MATERIAL INTO LUNGS, DUE TO VOMITING, CAN CAUSE CHEMICAL PNEUMONITIS.

INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. GIVE ARTIFICIAL RESPIRATION IF NECESSARY. GET MEDICAL ATTENTION.

SECTION V: REACTIVITY DATA

STABILITY DATA: STABLE

INCOMPATIBILITY: STRONG ALKALIES, OXIDIZERS, ALUMINUM & OTHER REACTIVE METALS

HAZARDOUS DECOMPOSITIONN PRODUCTS: HIGH TEMPS: POSSIBLE TRACE AMTS PHOSGENE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI: SPILL OR LEAK PROCEDURES

SMALL SPILLS: SOAK UP ON APPROPRIATE ABSORBENT MATERIAL

LARGE SPILLS: N/A

AVOID BREATHING OF VAPORS AND ABSORPTION THROUGH SKIN.

FOLLOW STATE AND LOCAL REGULATIONS FOR DISPOSAL OF LARGE NON-RECLAIMABLE SPILLS.

SECTION VII: SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

APPROVED ORGANIC TYPE REPPIRATOR IF CONCENTRATION IS 350-1000 PPM

VENTILATION: SUFFICIENT GENERAL AND/OR LOCAL EXHAUST

PROTECTIVE GLOVES: NEOPRENE, NITRILE RUBBER, POLYVINYL CHLORIDE

EYE PROTECTION: CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS

OTHER PROTECTIVE EQUIPMENT:NONE

WASH HANDS BEFORE EATING. DO NOT EAT, DRINK, OR SMOKE IN WORK AREA.

SECTION VIII: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

DO NOT STORE AT TEMPERATURES ABOVE 120 F. KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS: READ & FOLLOW THE DIRECTIONS ON THE PRODUCT LABEL. THEY ARE YOUR BEST GUIDE TO USING THIS PRODUCT IN THE MOST EFFECTIVE MANNER, AND THEY ALSO GIVE YOU THE NECESSARY SAFETY PRECAUTIONS TO PROTECT YOUR HEALTH.